BUY ONLINE

Filtration Products



Diesel Cetane Boost improves combustion efficiency to increase power in diesel engines.

Diesel Cold Flow Improver helps prevent icing or gelling in fuel.

Diesel Injector Clean removes performance-robbing deposits from diesel fuel injectors to restore horsepower and improve fuel economy.

Diesel Recovery quickly liquefies gelled diesel fuel and thaws frozen fuel filters.

Ea® Heavy-Duty Extended-Life Oil Filters provide maximum engine protection with filtering efficiency of 98.7 at 20 microns.



Contact your full-service AMSOIL Dealer for more information on AMSOIL products or to place an order. You may also order direct by calling AMSOIL INC. at 1-800-956-5695 and providing the referral number listed here. ◆

dditives and

Referral #



It's hard enough to make money farming without the hassle of equipment breakdowns. Unpredictable weather and volatile commodity prices may be out of your control, but you can help reduce the time and money spent on repairs by implementing a maintenance program centered around AMSOIL synthetic lubricants. Conventional lubricants don't hold up when heavy hauling, extreme temperatures, excessive idling, dirt and other challenges are the norm. AMSOIL synthetic lubricants, on the other hand, are formulated for the toughest operating conditions farmers encounter. They help you increase equipment life and profitability.

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied.

- Maximize equipment life & performance
- Help reduce breakdowns
- **Excellent** severe-service performance



G3156 3/17

is made by their use. All products advertised here are developed by AMSOIL for use in the applications shown Order by Phone 1-800-956-5695 - Give Operator Reference #1708529

Synthetic Diesel Oil



AMSOIL Signature Series Max-Duty Synthetic Diesel Oil

- Our most advanced formula
- 6X more engine protection*
- Compatible with all exhaust treatment devices
- Available in 5W-30, 0W-40, 5W-40 and 15W-40

*Than required by the Detroit Diesel DD13 Scuffing Test for Specification DFS 93K222



AMSOIL Heavy-Duty Synthetic Diesel Oil

- Excellent protection and performance
- 4X more engine protection*
- · Compatible with all exhaust treatment devices
- Available in 10W-30, 5W-40 and 15W-40

*Than required by the Detroit Diesel DD13 Scuffing Test for Specification DFS 93K222

Synthetic Hydraulic/ **Transmission Fluid**

- Long component life in severe service
- All-weather formulation resists extreme heat & cold
- Suppresses wet-brake chatter

MS TIS

Gear Lube

 Recommended for most brands of equipment

Qualifies as a Universal Tractor

1511

All Weether SAE SW-30

Transmission Oil A typical Universal Tractor Transmission (UTTO)

Oil (UTTO) has to simultaneously lubricate gears and hydraulic system components, support the wet braking system, inhibit corrosion, resist water and act as a medium for generating elevated hydraulic pressures to operate ancillary equipment. The lubricant's performance is especially critical to proper operation of hydrostatic transmissions. It takes a precision formulation to meet these demands, and AMSOIL formulates Synthetic Hydraulic/Transmission Fluid with the advanced synthetic technology needed to maximize equipment performance and life.

Synthetic Hydraulic Oil



- Promotes reduced maintenance • All-season performance
- Anti-varnish, anti-wear
- Maximizes efficiency

Hydraulic systems in tractors and other farm equipment require clean, high-quality fluid to function reliably. Without it, extreme heat can cause damaging varnish formation that can reduce fluid flow, plug filters, stick valves and increase friction, while wear to pumps, motors and valves can lead to catastrophic failure. AMSOIL synthetic hydraulic oils promote long life of individual components while maximizing the efficiency of the entire hydraulic system. They help reduce repairs and maximize profitability.



Aluminum Beaker Oxidation Test Tested April 2012

CONVENTIONAL **HYDRAULIC OIL (ISO 46)**



AMSOIL MULTI-VISCOSITY SYNTHETIC HYDRAULIC OIL (ISO 46)

In severe oxidation testing, AMSOIL Multi-Viscosity Synthetic Hydraulic Oil resisted elevated heat and oxidation more effectively than the conventional fluid. It helps hydraulic system components stay clean, operate reliably and last long.

Order by Phone 1-800-956-5695 - Give Operator Reference #1708529

Synthetic Gear Lube

 High-load protection for gears & bearings

• Long oil & equipment life

Helps reduce maintenance

Synthetic Grease · Resists extreme loads and impacts in heavily loaded equipment

SYNTHETIC POLYMERIC GREASE REASE

SVINE

Seals out contaminants

Protects against corrosion